



Seriously 4WD

www.tjm.com.au



NEW & IMPROVED TJM OX ELECTRIC WINCHES

FEATURES & BENEFITS

- Integrated solenoid control pack
- Illuminated controls (IP67 Plugs)
- High output series wound motor
- Planetary gear system
- Automatic load holding brake
- FRP sheath protecting all cables
- Free spooling
- Power in & power out
- Low electric current
- 3/8inch x 92ft aircraft cable (Nominal 14,400lbs)
- Anti-corrosive coated roller fairlead

LINE SPEED & AMP DRAW (FIRST LAYER)

	Line Load LBS/KGS	CM	Line Speed MPM	FPM	Motor Current
TJM OX 12,000LB ELECTRIC	0/0	600	6.0	19.7	70.0
	2000/907	348	3.5	11.4	125.0
	4000/1814	224	2.2	7.3	190.0
	6000/2722	174	1.7	5.7	230.0
	8000/3629	124	1.2	4.1	279.0
	10000/4536	96	1.0	3.1	334.0
12000/5443	80	0.8	2.6	362.0	
TJM OX 9,500LB ELECTRIC	0/0	560	5.6	18.3	81.0
	2000/907	338	3.4	11.0	134.0
	4000/1814	228	2.3	7.4	191.0
	6000/2722	164	1.6	5.3	228.0
	8000/3629	114	2	3.7	275.0
	9500/4309	92	0.9	3.0	298.0
TJM OX 8,500LB ELECTRIC	0/0	716	7.16	23.5	72.0
	2000/907	400	4	13.1	133.0
	4000/1814	288	2.88	9.4	171.0
	6000/2722	264	2.64	8.7	220.0
	8500/3855	132	1.32	4.3	303.0



Illuminated controls (IP67 Plugs)



FRP Sheath protection

TJM OX 12,000LB ELECTRIC	Single Line Rated Pull	12000Lbs (5443kg) Single-Line	Fairlead	4-Way Roller Fairlead
	Motor	5.5hp/4.0kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	218:1	Finish	Dark Grey
	Clutch	Sliding Ring Gear	Weight	N.W. 88lbs (40.0kg) G.W. 95lbs (43kg)
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 21.2" x 6.3" x 8.0" (541 x 160 x 203mm)
	Drum Size	Diameter 63.5mm, Length 224mm	Mounting Bolt Pattern	10.00±0.015" x 4.50±0.010" (254 x 114.3mm)
Cable	28m of 9.5mm Diameter			
TJM OX 9,500LB ELECTRIC	Single Line Rated Pull	9500Lbs (4080kg) Single-Line	Fairlead	4-Way Roller Fairlead
	Motor	5.5hp/4.0kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	196:1	Finish	Black Onyx
	Clutch	Sliding Ring Gear	Weight	80.5lbs (36.5kg)
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 21.2" x 6.3" x 8.0" (537 x 160 x 203mm)
	Drum Size	Diameter 63.5mm, Length 222mm	Mounting Bolt Pattern	10.00±0.015" x 4.50±0.010" (254 x 114.3mm)
Cable	28m of 8.2mm Diameter			
TJM OX 8,500LB ELECTRIC	Single Line Rated Pull	8500Lbs (3630kg) Single-Line	Fairlead	4-Way Roller Fairlead
	Motor	5.5hp/4.0kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	176:1	Finish	Black Onyx
	Clutch	Rotating Ring Gear	Weight	80.5lbs (36.5kg)
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 22" x 6.3" x 8.1" (557 x 160 x 205mm)
	Drum Size	Diameter 63.5mm, Length 222mm	Mounting Bolt Pattern	10.00±0.015" x 4.50±0.010" (254 x 114.3mm)
Cable	28m of 8.2mm Diameter			

MODEL: TJM OX WINCHES

DESC: 12,000LB OX WINCH

PN: 947Mox12000

DESC: 9,500LB OX WINCH

PN: 947Mox9500

DESC: 8,500LB OX WINCH

PN: 947Mox8500

08
147

AVAILABLE NOW