



Seriously 4WD

www.tjm.com.au

V-9

V-10

V-12



SUPREME CONSTRUCTION. SUPREME PERFORMANCE.
THE MILE MARKER V-SERIES IS THE TOUGHEST & MOST ADVANCED ELECTRIC WINCHES ON THE MARKET



MILE MARKER
 ABUSED WORLD WIDE

NEW MILE MARKER V SERIES ELECTRIC WINCHES

FEATURES & BENEFITS

- 100% Mosfet controlled
- Variable speed retrieval
- IP67 waterproof electric sealing
- Anti corrosive coating
- Illuminated joystick control
- Low voltage power down
- Solid state control box
- Plasma rope compatible
- High protection cable coating
- High output motors (Series wound)
- Automatic load holding brake
- 4 positional motor clock mounting
- 18 positional clock mounting on clutch handle
- Power in and power out
- Planetary gear system for fast line speed
- FRP sheathing protection to all electric cables
- Roller Fairlead coated in Dacromet® finish



Illuminated variable speed control (IP67 Plugs)



FRP Sheath protection

V12	Single Line Rated Pull	12000Lbs (5443kg) Single-Line	Fairlead	4-Way Roller Fairlead with Dacromet® coating
	Motor	6.5hp/4.8kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	212:1	Finish	Two-Compound Polyurethane Coating (Black)
	Clutch	Sliding Ring Gear	Weight	34.8kg
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 591.4 x 170 x 223.9mm
	Drum Size	Diameter 63.5mm, Length 224mm	Mounting Bolt Pattern	254 x 114.3mm
Cable	28m of 9.5mm Diameter			
V10	Single Line Rated Pull	10,000Lbs (4535kg) Single-Line	Fairlead	4-Way Roller Fairlead with Dacromet® coating
	Motor	5.5hp/4.0kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	212:1	Finish	Two-Compound Polyurethane Coating (Black)
	Clutch	Sliding Ring Gear	Weight	33.2kg
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 571 x 170 x 223.9mm
	Drum Size	Diameter 63.5mm, Length 222mm	Mounting Bolt Pattern	254 x 114.3mm
Cable	28m of 8.2mm Diameter			
V9	Single Line Rated Pull	9000Lbs (4082kg) Single-Line	Fairlead	4-Way Roller Fairlead with Dacromet® coating
	Motor	4.5hp/3.3kw, Series Wound	Remote Control	Included
	Control	Remote Switch, 12ft(3.7m) Lead	Battery	Recommended: 650CCA Minimum for Winching
	Gear Train	3 Stage Planetary	Battery Leads	2 Gauge, 1.6m
	Gear Reduction Ratio	212:1	Finish	Two-Compound Polyurethane Coating (Black)
	Clutch	Rotating Ring Gear	Weight	30kg
	Braking Action	Automatic In-The-Drum	Overall Dimensions	(LxWxH) 571 x 170 x 223.9mm
	Drum Size	Diameter 63.5mm, Length 222mm	Mounting Bolt Pattern	254 x 114.3mm
Cable	28m of 8.2mm Diameter			

MODEL: MILE MARKER WINCHES

DESC: V12 ELECTRIC WINCH

PN: 947MILEV12

DESC: V10 ELECTRIC WINCH

PN: 947MILEV10

DESC: V9 ELECTRIC WINCH

PN: 947MILEV9

08
150

AVAILABLE NOW